

Luotettavat Asco magneettiventtiilit monenlaisiin käyttöolosuhteisiin ja useille väliaineille.

210



238



256



327



202



220



290



*Muutos parempaan –
valitse Sitek ja
Asco magneettiventtiilit*



Asco magneettiventtiilit



210-sarja

Ilma, vesi, öljy
2/2 NC
max 9 bar AC (3-6 bar DC)

Koko	nd	Kv	min bar	Koodi
3/8"	16	2,6	0	SCE210C93
1/2"	16	3,4	0	SCE210C94
3/4"	19	4,3	0	SCE210D95
1"	25	11,1	0	SCE210B154
1 1/4"	28	12,8	0	SCE210B155
1 1/2"	32	19,3	0	SCE210B156

DC (=) : 24 V – 48 V

AC (~) : 24 V – 48 V – 115 V – 230 V /50 HZ

Esim. SCE210C94.24/DC



238-sarja

Ilma, vesi
2/2 NC
max 10 bar AC/DC

Koko	nd	Kv	min bar	Koodi
3/8"	12	2,4	0,3	SCE238A001
1/2"	15	4,2	0,3	SCE238B003
3/4"	20	6,6	0,3	SCE238A004
1"	25	9,9	0,3	SCE238A005
1 1/4"	30	15	0,5	SCG238C016
1 1/2"	45	27	0,5	SCG238C017
2"	45	34	0,5	SCG238C018

DC (=) : 24 V – 48 V

AC (~) : 24 V – 48 V – 115 V – 230 V /50 HZ

Esim. SCG238A004.230/50



256-sarja

Ilma, vesi, öljy
2/2 NC
max 20 bar AC (12 bar DC)

Koko	nd	Kv	min bar	Koodi
1/8"	1,6	0,08	0	SCG256A002VMS

DC (=) : 24 V – 48 V

AC (~) : 24 V – 48 V – 115 V – 230 V /50 HZ

Esim. SCG256A002VMS.115/50



327-sarja

Ilma, vesi, öljy
3/2 NC
max 10 bar AC/DC

Koko	nd	Kv	min bar	Koodi
1/4"	5,7	0,43	0	SCB327A001

DC (=) : 24 V – 48 V

AC (~) : 24 V – 48 V – 115 V – 230 V /50 HZ

Esim. SCB327A001.48/DC



202-sarja

Ilma, vesi, öljy
2/2 NC
max 4-8 bar DC

Koko	nd	Kv	min bar	Koodi
1/4"	2,4	0,05	0	SCG202A002V
1/4"	3,2	0,12	0	SCG202A003V
1/4"	2,4	0,05	0	SCG202A052V
1/4"	3,2	0,12	0	SCG202A053V

DC (=) : 24 V

Esim. SCG202A052V.24/DC



220-sarja

Höyry, kuuma vesi
2/2 NC
max 10 bar AC

Koko	nd	Kv	min bar	Koodi
3/8"	16	2,6	0,35	SCE220A019
1/2"	16	3,5	0,35	SCE220A021
3/4"	19	4,3	0,35	SCE220A023
1"	25	11,6	0,35	SCE220-025

AC (~) : 24 V – 48 V – 115 V – 230 V /50 HZ

Esim. SCE220A023.115/50



290-sarja

Ilma, vesi, öljy
2/2 NC
max 6-16 bar

Koko	nd	Kv	min bar	Koodi (pronssi)	Koodi (ruostumaton)	Pilottiventtiili
3/8"	10	2,8	0		E290A791	189/356
1/2"	15	4,9	0	E290B002	E290B045	189/356
3/4"	20	9,4	0	E290B005	E290B048	189/356
1"	25	16,5	0	E290B010	E290B056	189/356
1 1/4"	32	27	0	E290A017	E290A060	374
1 1/2"	40	45	0	E290A021	E290A064	374
2"	50	66	0	E290A485	E290A498	374
2 1/2"	65	111	0	E290A488	E290A501	374

DC (=) : 24 V – 48 V

AC (~) : 24 V – 48 V – 115 V – 230 V /50 HZ

Kysy tarvittaessa myös muita jännitteitä.